

Pumps



50ZB26-4Q



50ZB26-4Q

80ZB30-4.8Q

Pump	Centrifugal	Centrifugal
Suction Port Diameter	50 mm (2 in)	80 mm (3 in)
Total Head	26 m	30 m
Suction Head	6 m	6 m
Delivery	420 L/min	800 L/min
Engine	5.5 HP 4-Stroke OHV Air Cooled Single Cylinder	6.5 HP 4-Stroke OHV Air Cooled Single Cylinder
Displacement	163 cc	196 cc
Starting System	Recoil	Recoil
Maximum Power Output	4.1 kw at 3,600 rpm	4.8 kw at 3,600 rpm
Rated Output	3.4 kw at 3,600 rpm	4 kw at 3,600 rpm
Oil Alert	Yes	Yes
Fuel Tank Capacity	3.6 L	3.6 L
Engine Oil Capacity	0.6 L	0.6 L
Dimensions: Length / Width / Height	42,5 x 32,5 x 41,5 cm (16,7 x 12,8 x 16,3 in)	45,5 x 32,5 x 42 cm (18 x 12,8 x 16,5 in)
Dry Weight	20 kg (44lb)	30 kg (66 lb)

Lifan's water pumps are efficient and energy saving. They are perfect for both professionals and homeowners.

Lifan's replacement engines are outstanding, affordable and ecological. They offer you many possibilities and they fit any application.

Lifan's products are covered by a one-year limited warranty. They are also certified by the EPA (Environment Protection Agency, USA).




Distributed by:

MTI
CANADA

MTI Canada inc.
1720, boul. de la Rive-Sud
Saint-Romuald QC G6W 5M6
www.mticanada.ca

Your dealer:



Pumps and Engines



Small Engines



LF 168F-2



	168F	168F-2	177F	182F / 182F-D*	188F / 188F-D*	190F-D
Engine Type	5.5 HP 4-Stroke OHV Air Cooled Single Cylinder	6.5 HP 4-Stroke OHV Air Cooled Single Cylinder	9 HP 4-Stroke OHV Air Cooled Single Cylinder	11 HP 4-Stroke OHV Air Cooled Single Cylinder	13 HP 4-Stroke OHV Air Cooled Single Cylinder	15 HP 4-Stroke OHV Air Cooled Single Cylinder
Displacement	163 cc	196 cc	270 cc	337 cc	389 cc	420 cc
Starting System	Recoil	Recoil	Recoil	Recoil	Recoil	Recoil and electric
Crankshaft PTO Diameter	20 mm	20 mm	25.4 mm	25.4 mm	25.4 mm	25.4 mm
Crankshaft Type	Key way	Key way	Key way	Key way	Key way	Key way
Compression Ratio	8.5:1	8.5:1	8.2:1	8.0:1	8.0:1	8.2:1
Bore / Stroke	68 mm x 45 mm	68 mm x 54 mm	77 mm x 58 mm	82 mm x 64 mm	88 mm x 64 mm	88 mm x 64 mm
Maximum Output Power	4 kW at 3,600 rpm	4.8 kW at 3,600 rpm	6.6 kW at 3,600 rpm	8 kW at 3,600 rpm	9.5 kW at 3,600 rpm	11.8 kW at 3,600 rpm
Rated Output	3.4 kW at 3,600 rpm	4 kW at 3,600 rpm	5.4 kW at 3,600 rpm	6.4 kW at 3,600 rpm	7.2 kW at 3,600 rpm	8.5 kW at 3,600 rpm
Maximum Torque	10 mN at 2,500 rpm	11 mN at 2,500 rpm	15.5 mN at 2,500 rpm	21 mN at 2,500 rpm	23 mN at 2,500 rpm	25 mN at 2,500 rpm
Ignition System	Transistor	Transistor	Transistor	Transistor	Transistor	Transistor
Air Cleaner	Dual Element	Dual Element	Dual Element	Dual Element	Dual Element	Dual Element
Fuel Tank Capacity	3.6 L	3.6 L	6 L	6.5 L	6.5 L	6.5 L
Engine Oil Capacity	0.6 L	0.6 L	1.1 L	1.1 L	1.1 L	1.1 L
Oil Alert	Yes	Yes	Yes	Yes	Yes	Yes
Dimensions: Length / Width / Height	31,2 x 36,2 x 33,5 cm (12,2 x 14,2 x 13,1 in)	31,2 x 36,2 x 33,5 cm (12,2 x 14,2 x 13,1 in)	38 x 43 x 41 cm (15 x 17 x 16,1 in)	40,5 x 45 x 44,3 cm (16 x 17,7 x 17,4 in)	40,5 x 45 x 44,3 cm (16 x 17,7 x 17,4 in)	40,5 x 45 x 44,3 cm (16 x 17,7 x 17,4 in)
Dry Weight	15 kg (33 lb)	16 kg (35 lb)	25 kg (55 lb)	31 kg (68 lb)	31 kg (68 lb)	36 kg (79 lb)

* Models 182F-D and 188F-D are equipped with both an recoil and an electric starter.