


Outreach (m)	4.2
Gross lifting torque (kNm)	26
Slewing torque (kNm)	7,8
Weight (kg)	510
Lifting capacity at 4m (kg), at 3 (m)	760
Lifting capacity at max.	
extent (kg)	540
Extension	N/A
Rotator	CR300
Control valve options	Mechanic


6100 2395 1850 4 m 6.1 m 580kg 350 kg

Outreach (m)	6.1
Gross lifting torque (kNm)	33
Slewing torque (kNm)	9
Weight (kg)	560
Lifting capacity at 4m (kg)	580
Lifting capacity at max.	
extent (kg)	350
Extension	Single
Rotator	CR300
Control valve options	Mechanic



Outreach (m)	6.9				
Gross lifting torque (kN	m) 46				
Slewing torque (kNm)	12				
Weight (kg)	630				
Lifting capacity at max. extent (kg) 450					
Extension	Single				
Rotator	CR300				
Control valve options	Mechanic, Pre-				
	hydraulic, Electric,				
	Remote control				

CR59



Outreach (m)		8.5
Gross lifting torque (k	Nm)	55
Slewing torque (kNm)		19
Weight (kg)		1060
Lifting capacity at 4m	(kg)	870
Lifting capacity at max	c extend (kg)	390
Extension		Double
Rotator		CR400
Control valve options	Mechanic, Pr	e-hydraulic
	Electric	



Outreach (m)		7.2
Gross lifting torque (kh	lm)	67
Slewing torque (kNm)		19
Weight (kg)		940
Lifting capacity at 4m (kg)	1150
Lifting capacity at max	extent (kg)	570
Extension		Single
Rotator		CR505
Control valve options	Mechanic, Pr	e-hydraulic
	Electric, Rem	note control

CR69+								
CR69	3 - 1 1150 1350	870 1040	760 900	- 6 - 1 590 710	3 - 7 - 1 500 600	- 8 - 1 420 510	8.5 390 470	m kg (190 ber) kg (215 ber*)

Outreach (m)		8.5		
Gross lifting torque (kh	lm)	67		
Slewing torque (kNm)		19		
Weight (kg)		1060		
Lifting capacity at 4m (kg)	870		
Lifting capacity at max	. extent (kg)	390		
Extension		Double		
Rotator		CR505		
Control valve options Mechanic, Pre-hydraulic				
	Flectric Rem	note control		

CR89		E			The same of	
)				
CR89	-3 - 4 1 1460 1180	5 — 5 — 930	- 6 1 760	7 — 8 630 54		m kg (190 bar)

Outreach (m)		9	
Gross lifting torque (kl	Nm)	75	
Slewing torque (kNm)		19	
Weight (kg)		1210	
Lifting capcity at 4m (kg	(g)	1180	
Lifting capacity at max	. extent (kg)	460	
Extension		Double	
Rotator		GV 6	
Control valve options	Pre-hydrauli	c, Electric	
	Remote control		

Farmi wood cranes have been designed for demanding logging activities, but they also suit for general agricultural use.

Our crane range is sure to provide customers with models optimal for their needs.





Distributed by:



Telephone: 418 839-4127 Toll Free: 1 866 718-4746 Fax: 1 800 363-7157