

STRAIGHT-FORWARD POWER AND PERFORMANCE.

A no-nonsense machine that's solid as steel, the Deluxe clears snow without question or compromise. Traverse the terrain with the ease of Auto-Turn steering technology, while a high, 21" housing, large impeller and 14" auger diameter take on up to 72 tons of snow per hour and send it flying up to 55 feet.



AUTO-TURN[™] STEERING

Zero-degree turning radius.

ENGINE

Reliable Ariens® AX engine.

AUGER

14" auger diameter.

DUAL-BELT DRIVE

Delivers maximum power and extended belt life.

SUPER HIGH OUTPUT (SHO)

Available SHO on the Deluxe 28 SHO throws up to 72 tons per hour.

EZ-LAUNCH[™] EFI ENGINE

Available EFI engine starts easier and uses less fuel with consistent power.

TIRES

16" directional tires provide improved mobility and agility.

DESIGNATION	DELUXE 30 EFI	DELUXE 30	DELUXE 28 SHO	DELUXE 28	DELUXE 24
MODEL #	921049	921047	921048	921046	921045
STAGE TYPE	Two Stage	Two Stage	Two Stage	Two Stage	Two Stage
ENGINE POWER	306cc EFI/E-Gov (15 ft/lbs)	306cc Gen 3 (15 ft/lbs)	306cc Gen 3 (15 ft/lbs)	254cc (12.5 ft/lbs)	254cc (12.5 ft/lbs)
ENGINE BRAND	Ariens AX EZ-Launch EFI	Ariens AX	Ariens AX	Ariens AX	Ariens AX
STARTING SYSTEM	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil	120V/Recoil
CLEARING WIDTH	30 in (76.2 cm)	30 in (76.2 cm)	28 in (71.2 cm)	28 in (71.2 cm)	24 in (60.1 cm)
HOUSING HEIGHT	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)	21 in (53.3 cm)
THROWING DISTANCE	3 ft - 50 ft (.9 - 15.2 m)	3 ft - 50 ft (.9 - 15.2 m)	3 ft - 55 ft (.9-16.7 m)	3 ft - 50 ft (.9 - 15.2 m)	3 ft - 50 ft (.9 - 15.2 m)
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°
CHUTE ROTATION	2.5x Ice Drill	2.5x Ice Drill	2.5x Ice Drill	2.5x Ice Drill	2.5x Ice Drill
DEFLECTOR CONTROL	Remote	Remote	Remote	Remote	Remote
TIRE SIZE	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)	16 in x 4.8 in (41 x 12 cm)
TIRE TYPE	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread
STEERING	Auto-Turn	Auto-Turn	Auto-Turn	Auto-Turn	Auto-Turn
DRIVE TYPE	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic	Disc-O-Matic
SPEEDS	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse	6 Forward / 2 Reverse
GEAR CASE	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
GEAR CASE WARRANTY	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm	5yr Cons, 1yr Comm
IMPELLER PROFILE	Steel 3 Blade	Steel 3 Blade	High Speed Steel 3 Blade	Steel 3 Blade	Steel 3 Blade
IMPELLER DIAMETER	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)
AUGER DIAMETER	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)	14 in (35.6 cm)
AUGER TYPE	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated	Steel Serrated
SKID SHOES	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible	Steel Reversible
SCRAPER BAR	Steel Adjustable	Steel Adjustable	Steel Adjustable	Steel Adjustable	Steel Adjustable
PRODUCT WARRANTY	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm	3yr Cons, 90 day Comm
LENGTH	58.3 in (148.1 cm)	58.3 in (148.1 cm)	58.6 in (148.8 cm)	58.6 in (148.8 cm)	58.6 in (148.8 cm)
WIDTH	32.4 in (82.3 cm)	32.4 in (82.3 cm)	29.9 in (115.1 cm)	29.9 in (75.9 cm)	26.4 in (67.1 cm)
HEIGHT	45.5 in (115.6 cm)	45.5 in (115.6 cm)	45.3 in (115.6 cm)	45.3 in (115.1 cm)	45.3 in (115.1 cm)
WEIGHT	275.6 lbs (125.0 kg)	275.6 lbs (125.0 kg)	267.5 lb (121.3 kg)	249.8 lbs (113.3 kg)	245.5 lbs (114.4 kg)
FEATURES AT A GLANCE	Halogen Headlight, Handwarmers, Remote Deflector, Electric Start, One Hand Interlock, EZ-Launch EFI Engine	Halogen Headlight, Handwarmers, Remote Deflector, Electric Start, One Hand Interlock	Halogen Headlight, Remote Deflector, Electric Start, One Hand Interlock, Super High Output	Halogen Headlight, Remote Deflector, Electric Start, One Hand Interlock	Halogen Headlight, Remote Deflector, Electric Start, One Hand Interlock



Registered trademark and "" trademark of AriensCo. Kawasaki", Kohler" and Hydro-Gear" are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2019 AriensCo. All rights reserved. 0119



MTI Canada

AN ARIENS CO BRAND