

2020 SPECIFICATIONS

EDGE[®] SERIES





STEP UP YOUR MOWING GAME.

Experience the comfort, convenience and versatility of a zero-turn mower backed by the quality and performance you expect from an Ariens. The Edge's intuitive controls help you maneuver in, around and through smaller yards with a fast, clean cut. Get your perfectly-manicured lawn and get back to your busy day faster with Ariens' legendary zero-turn engineering in your garage.



DESIGNATION	EDGE 34	EDGE 34	EDGE 42	EDGE 42	EDGE 52
MODEL #	915243	915251	915245	915253	915254
ENGINE	Kohler® 6000 Series™	Briggs Intek	Kohler® 6000 Series™	Briggs Intek	Kawasaki® FR651
HORSEPOWER	19 hp	20 hp	19 hp	20 hp	21.5 hp
DISPLACEMENT (CC)	660 cc	656 cc	660 cc	656 cc	726 cc
DRIVE SYSTEM	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles
FUEL CAPACITY	2 Gallon (7.5L)	2 Gallon (7.5L)	2 Gallon (7.5L)	2 Gallon (7.5L)	2 Gallon (7.5L)
GROUND SPEED (APPROXIMATE MPH) (FWD/REV)	6 mph / 3 mph	6 mph / 3 mph	6 mph / 3 mph	6 mph / 3 mph	6 mph / 3 mph
STARTER	Electric	Electric	Electric	Electric	Electric
CARB COMPLIANT	No	No	No	No	No
DECK MATERIAL	12 ga	12 ga	11ga	11ga	11ga
DECK CONSTRUCTION	Stamped	Stamped	Fabricated	Fabricated	Fabricated
NUMBER OF SPINDLES	2	2	2	2	3
BLADE TIP SPEED (FPM)	17,000	17,000	17,000	17,000	17,000
SPINDLE MATERIAL	Steel	Steel	Steel	Steel	Steel
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Sealed	Sealed	Sealed	Sealed	Sealed
DECK DRIVE	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	34 in	34 in	42 in	42 in	52 in
CUTTING HEIGHTS	1.5 in - 4.5 in	1.5 in - 4.5 in	1.5 in - 4.5 in	1.5 in - 4.5 in	1.5 in - 4.5 in
CUTTING POSITIONS	7	7	7	7	7
WHEELS FRONT AXLE	Fixed	Fixed	Fixed	Fixed	Fixed
WHEELS (FRONT)	11 in x 4 in	11 in x 4 in	11 in x 4 in	11 in x 4 in	11 in x 4 in
WHEELS (BACK)	18 in x 6.5 in - 8 in	18 in x 6.5 in - 8 in	20 in x 8 in - 8 in	20 in x 8 in - 8 in	20 in x 8 in - 8 in
SEAT	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs	High Back w/ Seat Springs
HOUR METER	Standard	Standard	Standard	Standard	Standard
WEIGHT	464 lbs	447 lbs	497 lbs	510 lbs	560 lbs
LENGTH	68 in	68 in	68 in	68 in	68 in
WIDTH	44.8 in	44.8 in	54.8 in	54.8 in	61.1 in
HEIGHT	39.3 in	39.3 in	40.5 in	40.5 in	40.5 in
WARRANTY (MACHINE)	2 Year / 150 Hour	2 Year / 150 Hour	2 Year / 150 Hour	2 Year / 150 Hour	2 Year / 150 Hour
ATTACHMENTS & ACCESSORIES	Non-Powered Bagger Kit, Mulching Kit, Trailer Hitch Kit, Spreader, Cart, Aerator, Dethatcher, Sprayer				

MOWER DECK

Choose from a 34-inch stamped deck, or a 42 or 52-inch fabricated deck.

COMFORT

The high back seat with natural airflow enhances operator comfort while keeping you cool.

DECK SYSTEM

A four-point deck lift system offers unmatched stability and consistent cutting.

INTUITIVE CONTROL

The Foot-operated deck lift offers quick and easy cutting height adjustment.

Registered trademark and "trademark of AriensCo. Kawasaki", Kohler* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2020 AriensCo. All rights reserved. 0120

AN ARIENS CO BRAND

Distribué par / Distributed by :



IKON XD SERIES





STRENGTH WITH A SOFTER SIDE.

With a solid tubular frame and a wide range of cutting sizes, the IKON XD brings power and flexibility to all yard sizes. A plush high back seat and large tires provide comfort and stability, hour after hour.



DESIGNATION	IKON XD 42	IKON XD 42	IKON XD 52	IKON XD 52	IKON XD 60
MODEL #	915265	915268	915266	915267	915273
ENGINE	Kohler® 7000 Series™	Kawasaki® FR600	Kohler® 7000 Series™	Kawasaki® FR691	Kawasaki® FR691
HORSEPOWER	22 hp	18 hp	24 hp	23 hp	23 hp
DISPLACEMENT (CC)	725 cc	603 cc	725 cc	726 cc	726 cc
DRIVE SYSTEM	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles	Hydro-Gear® EZT Transaxles
FUEL CAPACITY	2.8 Gallon (10.5L)	2.8 Gallon (10.5L)	2.8 Gallon (10.5L)	2.8 Gallon (10.5L)	2.8 Gallon (10.5L)
GROUND SPEED (APPROXIMATE MPH) (FWD/REV)	7 mph /3 mph	7 mph / 3 mph	7 mph / 3 mph	7 mph / 3 mph	7 mph / 3 mph
STARTER	Electric	Electric	Electric	Electric	Electric
CARB COMPLIANT	No	No	No	No	No
DECK MATERIAL	11 ga	11 ga	11 ga	11 ga	11 ga
DECK CONSTRUCTION	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated
NUMBER OF SPINDLES	3	3	3	3	3
BLADE TIP SPEED (FPM)	17,000	17,000	17,000	17,000	17,000
SPINDLE MATERIAL	Steel	Steel	Steel	Steel	Steel
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Sealed	Sealed	Sealed	Sealed	Sealed
DECK DRIVE	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Warner	Electric Warner	Electric Warner	Electric Warner	Electric Warner
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	42 in	42 in	52 in	52 in	60 in
CUTTING HEIGHTS	1.5 in-4.5 in	1.5 in-4.5 in	1.5 in-4.5 in	1.5 in-4.5 in	1.5 in-4.5 in
CUTTING POSITIONS	13	13	13	13	13
WHEELS FRONT AXLE	Fixed	Fixed	Fixed	Fixed	Fixed
WHEELS (FRONT)	11 in x 4 in - 5 in	11 in x 4 in - 5 in	11 in x 4 in - 5 in	11 in x 4 in - 5 in	11 in x 6 in - 5 in
WHEELS (BACK)	20 in x 8 in - 8 in	20 in x 8 in - 8 in	20 in x 10 in - 8 in	20 in x 10 in - 8 in	20 in x 10 in - 8 in
SEAT	High Back w/ Armrests	High Back w/ Armrests	High Back w/ Armrests	High Back w/ Armrests	High Back w/ Padded Armrests
HOUR METER	Standard	Standard	Standard	Standard	Standard
WEIGHT	592 lbs	594 lbs	637 lbs	639 lbs	671 lbs
LENGTH	77.5 in	77.5 in	77.5 in	77.5 in	77.5 in
WIDTH	54.2 in	54.2 in	63.4 in	63.4 in	72.2 in
HEIGHT	40 in	40 in	40 in	40 in	40 in
WARRANTY (MACHINE)	3 Year / 300 Hour	3 Year / 300 Hour	3 Year / 300 Hour	3 Year / 300 Hour	3 Year / 300 Hour
ATTACHMENTS & ACCESSORIES	2 Bucket Bagger Kit, Mulching Kit, Trailer Hitch Kit, Headlight Kit, Spreader, Roller, Aerator, Dethatcher, Sprayer				

COMMERCIAL-STYLE DECK

4" deep fully fabricated with advanced airflow for an exceptional cutting performance.

TUBULAR STEEL FRAME

The Fully-welded steel frame provides strength and durability.

DIAL-OPERATED CUTTING HEIGHT

13 cutting positions at your fingertips allows for easy adjustments from 1 ½" to 4 ½" cutting height with the turn of a dial.

HYDROSTATIC EZT TRANSAXLE

Transaxles provide increased torque and a smooth operation for better control .

PLUSH SEAT

Options like the plush, adjustable highback seat with padded armrests allows for longer use and greater comfort.

Registered trademark and "trademark of AriensCo. Kawasaki", Kohler* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2020 AriensCo. All rights reserved. 0120 AN ARIENS CO BRAND

Distribué par / Distributed by :



MTI Canada Tél. / tel.: 418 839-4127 Français: 1 800 463-4398 English: 1 800 463-7205 Téléc. / Fax: 1 800 363-7157

APEX[®] SERIES





POWER THROUGH WITH APEX.

The APEX powers through the toughest mowing environments with the strength of professional engineering and the comfort you expect from an Ariens. As a residential zero turn, the APEX is in a class by itself with intuitive controls for precision performance.



DESIGNATION	APEX 48	APEX 52	APEX 60
MODEL #	991161	991159	991163
ENGINE	Kohler® 7000 Series™	Kawasaki® FR691	Kawasaki® FR730
HORSEPOWER	23 hp	23 hp	24 hp
DISPLACEMENT (CC)	725 cc	726 cc	726 cc
DRIVE SYSTEM	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles
FUEL CAPACITY	5.1 Gallon (19.3L)	5.1 Gallon (19.3L)	5.1 Gallon (19.3L)
GROUND SPEED (APPROXIMATE MPH) (FWD/REV)	8 mph / 4 mph	8 mph / 4 mph	8 mph / 4 mph
STARTER	Electric	Electric	Electric
CARB COMPLIANT	No	No	No
DECK MATERIAL	10 ga	10 ga	10 ga
DECK CONSTRUCTION	Fabricated	Fabricated	Fabricated
NUMBER OF SPINDLES	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000
SPINDLE MATERIAL	Forged Aluminum	Forged Aluminum	Forged Aluminum
SPINDLE SHAFT	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing
DECK DRIVE	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Ogura	Electric Ogura	Electric Ogura
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	48 in	52 in	60 in
CUTTING HEIGHTS	1.5 in-5 in	1.5 in-5 in	1.5 in-5 in
CUTTING POSITIONS	15	15	15
WHEELS FRONT AXLE	Fixed	Fixed	Fixed
WHEELS (FRONT)	13 in x 6.5 in - 6 in	13 in x 6.5 in - 6 in	13 in x 6.5 in - 6 in
WHEELS (BACK)	22 in x 10 in - 12 in	22 in x 10.5 in - 12 in	22 in x 12 in - 12 in
SEAT	High Back Premium w/ Padded Armrests	High Back Premium w/ Padded Armrests	High Back Premium w/ Padded Armrests
HOUR METER	Standard	Standard	Standard
WEIGHT	825 lbs	850 lbs	870 lbs
LENGTH	79 in	79 in	79 in
WIDTH	63 in	67 in	75 in
HEIGHT	47 in	47 in	49 in
WARRANTY (MACHINE)	4 Year / 500 Hour	4 Year / 500 Hour	4 Year / 500 Hour
ATTACHMENTS & ACCESSORIES	2 Bucket Power Bagger Kit, Mulching Kit, Dis Sprayer, Folding ROPS Kit	scharge Cover Kit, Trailer Hitch Kit, Headlight Ki	t, Spreader, Roller, Aerator, Dethatcher,

10-GAUGE WELDED DECK

Fully fabricated 5 $1\!\!/\!\!2''$ deck offers superior airflow and exceptional cutting performance.

SOLID FRAME

Industry-leading, fully-welded tubular frame supports the overall design.

DECK LIFT SYSTEM

Foot-operated spring-assisted lift lets you effortlessly adjust between 15 cutting positions.

SELF ADJUSTING BELT DRIVE

Minimizes wear and tear with little to no maintenance required.

LARGE TIRES

22" rear and 13" front tires provide solid traction and a comfortable ride.

COMFORT FEATURES

High-back plush seats with padded arm rests provide all-day comfort.

Registered trademark and "trademark of AriensCo. Kawasaki", Kohler* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2020 AriensCo. All rights reserved. 0120

AN ARIENS CO BRAND

Distribué par / Distributed by :



MTI Canada Tél. / tel.: 418 839-4127 Français: 1 800 463-4398 English: 1 800 463-7205

Téléc. / Fax: 1 800 363-7157

ZENITH





PROFESSIONAL PERFORMANCE.

With a commercially-proven frame, the ZENITH is built to take on multiple yards with comfort features like a plush seat and isolators to keep you going all day.



DESIGNATION	ZENITH 60
MODEL #	991158
ENGINE	Kawasaki® FX730V
HORSEPOWER	24 HP
DISPLACEMENT (CC)	726 cc
DRIVE SYSTEM	Hydro-Gear® ZT-3100 Transaxles
FUEL CAPACITY	5.1 Gallon (19.3L)
GROUND SPEED (APPROXIMATE MPH) (FWD/REV)	8 mph / 4 mph
STARTER	Electric
CARB COMPLIANT	No
DECK MATERIAL	10 ga
DECK CONSTRUCTION	Fabricated
NUMBER OF SPINDLES	3
BLADE TIP SPEED (FPM)	18,000
SPINDLE MATERIAL	Forged Aluminum
SPINDLE SHAFT	Steel
SPINDLE BEARINGS	Ball Bearing
DECK DRIVE	Belt
DECK ENGAGEMENT	Electric Ogura
DECK LIFT SYSTEM	Foot Operated
CUTTING WIDTH	60 in
CUTTING HEIGHTS	1.5 in-5 in
CUTTING POSITIONS	15
WHEELS FRONT AXLE	Fixed
WHEELS (FRONT)	13 in x 6.5 in - 6 in
WHEELS (BACK)	22 in x 12 in - 12 in
SEAT	High Back Premium w/ Padded Armrests and Seat Isolation
HOUR METER	Standard
WEIGHT	953 lbs
LENGTH	81 in
WIDTH	75 in
HEIGHT	49 in
WARRANTY (MACHINE)	4 Year / 750 Hour
ATTACHMENTS & ACCESSORIES	2 Bucket Power Bagger Kit, Mulching Kit, Discharge Cover Kit, Trailer Hitch Kit, Headlight Kit

COMMERCIAL ENGINE

A Kawasaki FX engine with canister air filtration.

BELT TENSION SYSTEM

Constant tension requires no adjustments and keeps blade tip speed consistent throughout the life of your belt.

CUT QUALITY

A deep airflow deck works with the blades to lift grass effectively, evenly and with reduced clumping.

POWER PLANT

Commercial Kawasaki FX engine comes with dual-canister filtration for added durability.

COMFORT

Isolator mounts under the seat absorb vibration, reducing the fatigue of an honest day's work.

DURABILITY

Fully-welded steel frame is both validated by our structural engineers and proven in the field.

Registered trademark and Trademark of AriensCo. Kawasaki*, Kohler* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2020 AriensCo. All rights reserved. 0120

AN ARIENS CO BRAND

Distribué par / Distributed by :



MTI Canada Tél. / tel.: 418 839-4127 Français: 1 800 463-4398 English: 1 800 463-7205

WALK BEHIND SERIES





TAKE THE HARD WORK OUT OF YARD WORK.

Built to deliver season after season, the Walk Behind series starts easy and cuts cleanly. The efficiency of the 3-in-1 cutting system leaves your lawn looking spotlessly clean.



DESIGNATION	LM 21" PUSH	LM 22" SELF-PROPELLED	LM 22" SELF-PROPELLED, ELECTRIC START
MODEL #	911157	911158	911159
ENGINE	Ariens	Ariens	Ariens
DISPLACEMENT (cc)	159 cc	159 cc	159 cc
DRIVE SYSTEM	Push	Variable Speed Rear Wheel Drive	Variable Speed Rear Wheel Drive
FUEL CAPACITY	0.26 Gallon (1L)	0.26 Gallon (1L)	0.26 Gallon (1L)
GROUND SPEED (APPROXIMATE MPH) (FWD/REV)	N/A	3 mph	3 mph
DECK MATERIAL	Steel	Steel	Steel
DECK CONSTRUCTION	Stamped	Stamped	Stamped
BLADE TIP SPEED (FPM)	17,043	17,855	17,855
DECK ENGAGEMENT	Fixed Blade	Fixed Blade	Fixed Blade
LIFT SYSTEM	Four Point	Single Point	Single Point
CUTTING WIDTH	21 in	22 in	22 in
CUTTING HEIGHTS	1.25 in - 3.4 in	1.5 in - 3.2 in	1.5 in - 3.2 in
CUTTING POSITIONS	5	8	8
WHEELS (FRONT)	8 in	8 in	8 in
WHEELS (BACK)	11 in	11 in	11 in
WEIGHT	72 lbs	92 lbs	110 lbs
LENGTH	35 in	41 in	41 in
WIDTH	24.25 in (w/ chute)	27.75 in (w/ chute)	27.75 in (w/ chute)
HEIGHT	17.75 in	20.75 in	20.75 in
WARRANTY (MACHINE)		3 Year Limited Residential	

MOWER DECK

Heavy-duty steel cutting deck is powdercoated to resist corrosion, offering a lifetime of durability.

CUTTING SYSTEM

3-in-1 cutting system flexes seamlessly between bagging, mulching or side discharge options.

CUT HEIGHT

Single-point cut height adjustments are quick and simple. (Available on self-propelled models only.)

WHEELS

8-inch front wheels and tall, 11-inch rear wheels add traction in uneven or rough terrain.

SELF-PROPELLED DRIVE

Rear wheel, self-propel feature provides superior traction in all cutting conditions.

Registered trademark and "trademark of AriensCo. Kawasaki", Kohler* and Hydro-Gear* are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2019 AriensCo. All rights reserved. 0119

AN **ARIENS** CO BRAND

Distribué par / Distributed by :

MTI Canada Tél. / tel.: 418 839-4127 Français: 1 800 463-4398 English: 1 800 463-7205 Téléc. / Fax: 1 800 363-7157

POWER BRUSH SERIES





THE DIFFERENCE IS CLEAR.

Sweep your driveway clean. The Ariens Power Brush clears slush, sleet, snow, leaves, sand and more all the way down to the pavement. The 40-degree pivoting brush head pushes it in the direction you want.



DESIGNATION	POWER BRUSH 28	POWER BRUSH 36	HYDRO POWER BRUSH 36
MODEL #	921056	926074	926075
ENGINE	Kohler® CH255	Kohler® CH395	Kohler® CH395
DISPLACEMENT (cc)	177 cc	277 cc	277 cc
STARTING SYSTEM	120V/Recoil	120V/Recoil	12V/Key
CLEARING WIDTH	28 in	36 in	36 in
BRUSH DIAMETER	18 in	25 in	25 in
BRUSH ROTATION ANGLE	40°	40°	40°
BRUSH ROTATION CONTROL	Remote Trigger	Remote Trigger	Remote Trigger
INTERLOCK CONTROL	Yes	Yes	Yes
TIRE SIZE	15 in x 5 in	16 in x 6.5 in	16 in x 6.5 in
TIRE TYPE	Directional Snow Tread	Directional Snow Tread	Directional Snow Tread
STEERING	Auto-Turn	Auto-Turn	Auto-Turn
FUEL TANK CAPACITY	0.95 Gal	1.58 Gal	1.58 Gal
DRIVE TYPE	Disc-O-Matic	Disc-O-Matic	Hydrostatic
SPEEDS	6 Forward/2 Reverse	6 Forward/2 Reverse	Variable
HALOGEN HEADLIGHT	No	Standard	Standard
HANDWARMERS	No	No	Standard
ELECTRIC START	Standard	Standard	Standard
WEIGHT	238 lbs	373 lbs	403 lbs
LENGTH	65 in	72 in	72 in
WIDTH	33 in	44 in	44 in
HEIGHT	44 in	43 in	43 in
WARRANTY	3 Year Limited Residential / 90 Day Limited Commercial	3 Year Limited Residential / 1 Year Limited Commercial	3 Year Limited Residential / 1 Year Limited Commercial
ATTACHMENTS & ACCESSORIES	Tur	f Caster Kit, Tire Chains, Snow Cab, Debris Deflec Bristle Replacement Kit, Wire Bristle Kit	ctor,

ALL-SEASON USE

From clearing the ice, snow and sludge in winter, to dethatching the lawn in spring, the power brush has use in any season.

HEIGHT ADJUSTMENT SYSTEM

Easily adjust the brush level to accommodate varying surfaces and minimize brush wear.

BRUSH ANGLE

With 40-degree brush head rotation and operator-controlled pivot lock, dirt and debris have no place to hide.

CLEAN TO PAVEMENT

The versatility of the power brush allows you to clean clear to the surface in any season and any condition.

Registered trademark and "trademark of AriensCo. Kawasaki", Kohler" and Hydro-Gear" are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit Ariens.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2019 AriensCo. All rights reserved. 0119

AN ARIENS CO BRAND

Distribué par / Distributed by :



MTI Canada Tél. / tel.: 418 839-4127 Français: 1 800 463-4398 English: 1 800 463-7205 Téléc. / Fax: 1 800 363-7157