



2020 | SPECIFICATIONS

SPECIFICATIONS

COMPACT-PRO[®] PRO-TURN[®] Z

	34	44
MODEL NUMBER	991144	991145
ENGINE	KAWASAKI [®] 481V FX, HEAVY DUTY AIR CLEANER	KAWASAKI [®] 600V FX
HORSEPOWER	15.5 HP	19 HP
DISPLACEMENT	603 CC	
DRIVE SYSTEM	HYDRO-GEAR [®] ZT-3100 TRANSAXLE	
FUEL CAPACITY	7.2 GAL.	
GROUND SPEED (APPROX.Mph)(Forward/Reverse)	7 MPH / 3 MPH	
STARTER	ELECTRIC	
DECK		
DECK MATERIAL	10 GA. STEEL WITH 10 GA. SPINDLE REINFORCEMENT	
DECK CONSTRUCTION	FABRICATED	
NUMBER OF SPINDLES	2	3
BLADE TIP SPEED (FPM)	17,270	
SPINDLEHOUSING MATERIAL	FORGED ALUMINUM	
SPINDLE BEARINGS	BALL BEARING	
DECK ENGAGEMENT	ELECTRIC OGURA [®] GT1.5	
DECK LIFT SYSTEM	FOOT OPERATED	
CUTTING WIDTH	34 IN.	44 IN.
CUTTING HEIGHT	1.0 IN. - 5.0 IN.	
CUTTING POSITIONS	17	
WHEELS		
FRONT AXLE	FIXED	
FRONT	SMOOTH 13 X 5-6	
REAR	21 X 7-10 TURF	20.5 X 8-10 TURF
FEATURES		
SEAT	HIGH BACK WITH EVC SUSPENSION	
FOLDABLE ROPS	OPTIONAL	
MACHINE		
WEIGHT	737 LBS.	789 LBS.
LENGTH	75 IN.	
WIDTH (W/O CHUTE)	35.9 IN.	46.7 IN.
WIDTH (W CHUTE)	48.3 IN.	56.9 IN.
HEIGHT	45.3 IN.	
WARRANTY		
UNIT	4 YEAR / 750 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS	
DECK SHELL & FRAME	N/A	
ATTACHMENTS & ACCESSORIES		
MULCHINGKIT,DISCHARGE COVERKIT,HUBCAPKIT,FLEXTENDSHOULDERSSUPPORTKIT,SOLIDTIREKIT,TRUE POWERTIREKIT,TRAILERHITCHKIT,HEADLIGHTKIT,STRIPINGKIT,PLUSHARMRESTKIT,SUNSHADEKIT,POWERED BAGGER KIT		

	48	52	60
MODEL NUMBER	991192	991194	991196
ENGINE	GRAVELY		
HORSEPOWER	26.5 HP		
DISPLACEMENT	764 CC		
DRIVE SYSTEM	HYDRO-GEAR [®] ZT-3100 TRANSAXLES		
FUEL CAPACITY	5.0 GAL.		
GROUND SPEED (APPROX.Mph)(Forward/Reverse)	8 MPH / 4 MPH		
DECK			
DECK MATERIAL	10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT		
DECK CONSTRUCTION	FABRICATED		
NUMBER OF SPINDLES	3		
BLADE TIP SPEED (FPM)	18,000		
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM		
SPINDLE BEARINGS	BALL BEARING		
DECK ENGAGEMENT	ELECTRIC OGURA [®]		
CUTTING WIDTH	48 IN.	52 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN. - 5.0 IN.		
CUTTING POSITIONS	15		
WHEELS			
FRONT AXLE	FIXED		
FRONT	SMOOTH 13 X 6.50-6		
REAR	TURF 22 X 10-12	TURF 22 X 10.5-12	TURF 22 X 12-12
FEATURES			
SAFETY	ANSI CERTIFIED		
SEAT	SEAT 20 IN. HIGH BACK COMFORT W/INTEGRATED ISOLATION		
FOLDABLE ROPS	STANDARD		
MACHINE			
WEIGHT	923 LBS.	932 LBS.	953 LBS.
LENGTH	79 IN.		
WIDTH (W/CHUTE UP/DOWN)	51 IN. / 63 IN.	55 IN. / 67 IN.	63 IN. / 75 IN.
HEIGHT (W/ROPS EXT/DOWN)	72 IN. / 52 IN.		
WARRANTY			
UNIT	4 YEAR COMMERCIAL / 750 HOUR LIMITED		
ATTACHMENTS & ACCESSORIES			
MULCHINGKIT,DISCHARGE COVERKIT,TRAILERHITCHKIT,HEADLIGHTKIT,STRIPINGKIT,SUNSHADEKIT,POWERED BAGGER KIT, OPERATOR CONTROLLED DISCHARGE CHUTE			



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-TURN[®] ZX

	48	52	60
MODEL NUMBER	991230	991232	991234
ENGINE	KAWASAKI [®] FX691V AIR-COOLED,VERTICALTWIN	KAWASAKI [®] FX691V AIR-COOLED,VERTICALTWIN	KAWASAKI [®] FX730V AIR-COOLED,VERTICALTWIN
HORSEPOWER	22 HP	22 HP	23.5 HP
DISPLACEMENT	726 CC	726 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR [®] ZT-3200 TRANSAXLES		
FUEL CAPACITY	5.0 GAL.		
GROUND SPEED (APPROX)(mph)(Forward/Reverse)	8.5 MPH / 4 MPH		
DECK			
DECK MATERIAL	10 GA. STEEL W/ 10 GA. SPINDLE REINFORCEMENT		
DECK CONSTRUCTION	FABRICATED		
NUMBER OF SPINDLES	3		
BLADE TIP SPEED (FPM)	18,000		
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM		
SPINDLE BEARINGS	BALL BEARING		
DECK ENGAGEMENT	ELECTRIC OGURA [®] GT1.5		
CUTTING WIDTH	48 IN.	52 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN. - 5.0 IN.		
CUTTING POSITIONS	15		
WHEELS			
FRONT AXLE	FIXED		
FRONT	SMOOTH 13 X 6.50-6		
REAR	TURF 22 X 10-12	TURF 22 X 10.5-12	TURF 22 X 12-12
FEATURES			
SEAT	20 IN. HIGH BACK COMFORT W/ INTEGRATED ISOLATION		
FOLDABLE ROPS	STANDARD		
MACHINE			
WEIGHT	924 LBS.	932 LBS.	953 LBS.
LENGTH	79 IN.		
WIDTH (W/O CHUTE)	51 IN.	55 IN.	63 IN.
WIDTH	63 IN.	67 IN.	75 IN.
HEIGHT(W/ROPSXT/DOWN)	72 IN. / 49 IN.		
WARRANTY			
UNIT	4 YEAR COMMERCIAL / 750 HOUR LIMITED		
ATTACHMENTS & ACCESSORIES			
2BUCKETPOWEREDBAGGER,MULCHINGKIT,DISCHARGECOVERKIT,TRAILERHITCHKIT,HEADLIGHTKIT,SUNSHADEKIT,SUSPENSION SEAT KIT, OPERATOR CONTROLLED DISCHARGE CHUTE			



Distribué par / Distributed by :
MTI
CANADA
MTI Canada
 Tél. / tel.: 418 839-4127
 Français: 1 800 463-4398
 English: 1 800 463-7205
 Téléc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-TURN® 100

	148	152	152	152	160	160	160	160
MODEL NUMBER	991128	991129	991132	991135	991130	991133	991136	991140
ENGINE	KAWASAKI® FX691V AIR-COOLED, HEAVY-DUTY AIR CLEANER	KAWASAKI® FX691V AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® ZT730 AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® ZT725 EFI AIR-COOLED, HEAVY-DUTY AIR CLEANER	KAWASAKI® FX730V AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® ZT740 AIR-COOLED, HEAVY-DUTY AIR CLEANER	KOHLER® ZT740 EFI AIR-COOLED, HEAVY-DUTY AIR CLEANER	YAMAHA® MX800V AIR-COOLED, HEAVY-DUTY AIR CLEANER
HORSEPOWER	22 HP	22 HP	23 HP	22 HP	23.5 HP	25 HP	25 HP	26 HP
DISPLACEMENT (CC)	726 CC	726 CC	747 CC	725 CC	726 CC	747 CC	747 CC	824 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3400 TRANSAXLES							
FUEL CAPACITY – Gallons(Liters)	10 GAL.							
GROUND SPEED (APPROX.Mph)(Forward/Reverse)	10 MPH / 5 MPH							
DECK								
DECK MATERIAL	7 GA. STEEL W/ 1/4 IN. SPINDLE REINFORCEMENT							
DECK CONSTRUCTION	FABRICATED							
NUMBER OF SPINDLES	3							
BLADE TIP SPEED (FPM)	18,000							
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM							
SPINDLE BEARINGS	BALL BEARING							
DECK ENGAGEMENT	OGURA® GT2.75 ELECTRIC CLUTCH							
CUTTING WIDTH	48 IN.	52 IN.	52 IN.	52 IN.	60 IN.	60 IN.	60 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN. - 5.5 IN.							
CUTTING POSITIONS	17							
WHEELS								
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES							
FRONT	SMOOTH 13 X 6.50-6							
REAR	TURF 23 X 10.50-12							
FEATURES								
SEAT	HIGH BACK W/ FULL SUSPENSION							
FOLDABLE ROPS	STANDARD							
MACHINE								
WEIGHT	1062 LBS.	1079 LBS.	1068 LBS.	1073 LBS.	1121 LBS.	1110 LBS.	1115 LBS.	1136 LBS.
LENGTH	78.5 IN.							
WIDTH (W/O CHUTE)	50 IN.		55.5 IN.				63 IN.	
WIDTH (W/ CHUTE)	62 IN.		67.5 IN.				75 IN.	
HEIGHT (W/ ROPS EXT/DOWN)	71 IN. / 48 IN.							
WARRANTY								
UNIT	5 YEAR / 1000 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS							
DECK SHELL & FRAME	LIMITED LIFETIME							
ATTACHMENTS & ACCESSORIES								
MULCHING KIT, DISCHARGE COVER KIT, HUB CAP KIT, SOLID TIRE KIT, TRUE POWER TIRE KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, SUNSHADE KIT, 2 BUCKET POWERED BAGGER KIT (8BU.)								



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-TURN[®] 200

	252	260	260	260	260	260	272
MODEL NUMBER	992268	992267	992269	992272	992281	992296	992270
ENGINE	KAWASAKI® FX850V AIR-COOLED HEAVY-DUTYAIRCLEANER	KOHLER® ZT740 AIR-COOLED HEAVY-DUTYAIRCLEANER	KAWASAKI® FX850V AIR-COOLED HEAVY-DUTYAIRCLEANER	KOHLER® EFI ECV860 AIR-COOLED HEAVY-DUTYAIRCLEANER	YAMAHA® EFI MXV775 AIR-COOLED HEAVY-DUTYAIRCLEANER	YAMAHA® MX825V AIR-COOLED HEAVY-DUTYAIRCLEANER	KAWASAKI® FX921V AIR-COOLED HEAVY-DUTYAIRCLEANER
HORSEPOWER	27 HP	25 HP	27 HP	29 HP	29 HP	27.5 HP	31 HP
DISPLACEMENT	852 CC	747 CC	852 CC	824 CC	824 CC	824 CC	999 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-5400 TRANSAXLES						
FUEL CAPACITY	13.4 GAL.						
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	13 MPH / 6 MPH						
DECK							
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT						
DECK CONSTRUCTION	FABRICATED						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	18,000						
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM						
SPINDLE BEARINGS	BALL BEARING						
DECK ENGAGEMENT	OGURA® GT3.5 ELECTRIC CLUTCH						
CUTTING WIDTH	52 IN.	60 IN.	60 IN.	60 IN.	60 IN.	60 IN.	72 IN.
CUTTING HEIGHTS	1.5 IN. - 5.5 IN.						
CUTTING POSITIONS	17						
WHEELS							
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES						
FRONT	SMOOTH 15 X 6-6						
REAR	TURF 23 X 10.5-12						TURF 24 X 12-12
FEATURES							
SEAT	HIGH BACK W/ FULL SUSPENSION & PADDED ARMRESTS						
FOLDABLE ROPS	STANDARD						
MACHINE							
WEIGHT (W/O FUEL)	1302 LBS.	1322 LBS.	1336 LBS.	1332 LBS.	1355 LBS.	1355 LBS.	1410 LBS.
LENGTH	80 IN.	80 IN.	80 IN.	80 IN.	80 IN.	80 IN.	82 IN.
WIDTH (W/O CHUTE)	55.5 IN.	63 IN.	63 IN.	63 IN.	63 IN.	63 IN.	75 IN.
WIDTH (W/ CHUTE)	67.5 IN.	75 IN.	75 IN.	75 IN.	75 IN.	75 IN.	87 IN.
HEIGHT (W/ ROPS EXT/DOWN)	70 IN. / 47.75 IN.						
WARRANTY							
UNIT	5 YEAR / 1250 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS						
DECK SHELL & FRAME	LIMITED LIFETIME						
ATTACHMENTS & ACCESSORIES							
3 BUCKET BAGGER (12 BU.), 12V OUTLET, SEAT ISOLATOR KIT, RADIAL DRIVE, TIRES, STRIPING KIT, OPERATOR-CONTROLLED DISCHARGE CHUTE, SEMI-PNEUMATIC FRONT TIRE KIT AND HEADLIGHT KIT							



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-TURN[®] MACH ONE

60

MODEL NUMBER	992297
ENGINE	KAWASAKI [®] FX921V
HORSEPOWER	31 HP
DISPLACEMENT	999 CC
DRIVE SYSTEM	HYDRO-GEAR [®] ZT-5400 TRANSAXLES
FUEL CAPACITY	13.4 GAL.
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	13 MPH / 6 MPH
DECK	
DECK MATERIAL	7 GA. STEEL W/ .25 IN. SPINDLE REINFORCEMENT
DECK CONSTRUCTION	WELDED
NUMBER OF SPINDLES	3
BLADE TIP SPEED (FPM)	18,633
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM
SPINDLE BEARINGS	BALL BEARING
DECK ENGAGEMENT	OGURA [®] GT3.5 ELECTRIC CLUTCH
CUTTING WIDTH	60 IN.
CUTTING HEIGHTS	1.5 IN. - 5.5 IN.
CUTTING POSITIONS	17
WHEELS	
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES
FRONT	SMOOTH 15 X 6-6 W/ GREASEABLE TAPERED ROLLER BEARINGS
REAR	TURF 24 X 12-12
FEATURES	
SEAT	HIGH BACK COMFORT W/ FULL SUSPENSION AND PADDED ARMRESTS
FOLDABLE ROPS	STANDARD
MACHINE	
WEIGHT	1375 LBS.
LENGTH	82 IN.
WIDTH (W/ CHUTE UP/DOWN)	61 IN. / 73 IN.
HEIGHT (W/ ROPS EXT/DOWN)	70 IN. / 47.75 IN.
GROUND CLEARANCE (UNDER REAR WHEELS)	4.5 IN.
WARRANTY	
UNIT	5 YEAR / 1250 HOUR COMMERCIAL / NO HOUR LIMIT FIRST TWO YEARS
DECK SHELL & FRAME	LIMITED LIFETIME
ATTACHMENTS & ACCESSORIES	
TRAILER HITCH KIT, HEADLIGHT KIT, SUN SHADE KIT, SOLID FRONT CASTER TIRE KIT, HUB CAP SET	



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télé. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-TURN® 400

	452	452	460	460	460	472	472
MODEL NUMBER	992273	992282	992275	992278	992283	992276	992284
ENGINE	KAWASAKI® FX850 AIR-COOLED, HEAVY-DUTYAIRCLEANER	YAMAHA® EFI MXV775 AIR-COOLED, HEAVY-DUTYAIRCLEANER	KAWASAKI® FX1000V AIR-COOLED, HEAVY-DUTYAIRCLEANER	KOHLER® EFI ECV880 AIR-COOLED, HEAVY-DUTYAIRCLEANER	YAMAHA® EFI MXV825 AIR-COOLED, HEAVY-DUTYAIRCLEANER	KAWASAKI® FX1000V AIR-COOLED, HEAVY-DUTYAIRCLEANER	YAMAHA® EFI MXV825 AIR-COOLED, HEAVY-DUTYAIRCLEANER
HORSEPOWER	27 HP	29 HP	35 HP	33 HP	33 HP	35 HP	33 HP
DISPLACEMENT	852 CC	824 CC	999 CC	824 CC	824 CC	999 CC	824 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-5400 TRANSAXLES						
FUEL CAPACITY	13.4 GAL.						
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	13 MPH / 6 MPH						
DECK							
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT						
DECK CONSTRUCTION	FABRICATED						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	18,000						
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM						
SPINDLE BEARINGS	BALL BEARING						
DECK ENGAGEMENT	OGURA® GT3.5 ELECTRIC CLUTCH						
CUTTING WIDTH	52 IN.	52 IN.	60 IN.	60 IN.	60 IN.	72 IN.	72 IN.
CUTTING HEIGHTS	1.0 IN. - 5.5 IN.						
CUTTING POSITIONS	19						
WHEELS							
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES						
FRONT	SMOOTH 15 X 6-6 SEMI PNEUMATIC						
REAR	RADIAL TURF 23 X 10-12	RADIAL TURF 23 X 10-12	RADIAL TURF 24 X 12-12	RADIAL TURF 24 X 12-12	RADIAL TURF 24 X 12-12	RADIAL TURF 24 X 12-12	RADIAL TURF 24 X 12-12
FEATURES							
SEAT	HIGH BACK W/ FULL AIR RIDE SUSPENSION AND SEAT ISOLATORS						
FOLDABLE ROPS	STANDARD						
MACHINE							
WEIGHT	1326 LBS.	1332 LBS.	1358 LBS.	1360 LBS.	1356 LBS.	1453 LBS.	1445 LBS.
LENGTH	80 IN.						
WIDTH (W/O CHUTE)	55.5 IN.	55.5 IN.	63 IN.	63 IN.	63 IN.	75 IN.	75 IN.
WIDTH (W/ CHUTE)	67.5 IN.	67.5 IN.	75 IN.	75 IN.	75 IN.	87 IN.	87 IN.
HEIGHT (W/ ROPS EXT/DOWN)	70/47.75 IN.						
WARRANTY							
UNIT	5 YEAR / 1500 HOUR COMMERCIAL / NO HOUR LIMIT FIRST 2 YEARS						
DECK SHELL & FRAME	LIMITED LIFETIME						
ATTACHMENTS & ACCESSORIES							
MULCHING KIT, DISCHARGE COVER KIT, HUB CAP KIT, FLEXTEND SHOULDER SUPPORT KIT, TRUE POWER TIRE KIT, TRAILER HITCH KIT, HEADLIGHT KIT, STRIPING KIT, 3 BUCKET BAGGER (12BU.)							



Distribué par / Distributed by :
MTI
CANADA
MTI Canada
Tél. / tel.: 418 839-4127
Français: 1 800 463-4398
English: 1 800 463-7205
Télééc. / Fax: 1 800 363-7157
www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-STANCE

	32FL	36FL	48FL	52FL	52FL	60FL	60FL
MODEL NUMBER	994157	994149	994150	994151	994152	994153	994154
ENGINE	KAWASAKI® FS 600 V-TWIN	KAWASAKI® FS 600 V-TWIN	KAWASAKI® FX 730 V-TWIN	KAWASAKI® FX 730 V-TWIN	KAWASAKI® FT EFI 730 V-TWIN	KAWASAKI® FX 730 V-TWIN	KAWASAKI® FT EFI 730 V-TWIN
HORSEPOWER	18.5 HP	18.5 HP	23.5 HP	23.5 HP	26 HP	23.5 HP	26 HP
DISPLACEMENT	603 CC	603 CC	726 CC	726 CC	726 CC	726 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3100 TRANSAXLE			HYDRO-GEAR® ZT-3400 TRANSAXLE			
FUEL CAPACITY	6 GAL.			9 GAL.			
GROUND SPEED (APPROX.Mph)(Forward/Reverse)	8 MPH / 3 MPH			9 MPH / 4 MPH			
STARTER	ELECTRIC						
DECK							
DECK MATERIAL	7 GA.						
DECK CONSTRUCTION	WELDED						
NUMBER OF SPINDLES	2			3			
BLADE TIP SPEED (FPM)	18,220			18,000			
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM						
SPINDLE BEARINGS	BALL BEARING						
DECK ENGAGEMENT	ELECTRIC CLUTCH						
DECK LIFT SYSTEM	MANUAL						
CUTTING WIDTH	32 IN.	36 IN.	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN. - 5.0 IN.						
CUTTING POSITIONS	15						
WHEELS							
FRONT	11 X 4.00-5 SEMI-PNEUMATIC			13 X 6.50-6 SEMI-PNEUMATIC			
REAR	18 X 6.50 - 8 RADIAL	18 X 8.50 - 8 RADIAL	20X10.50-8 RADIAL				
MACHINE							
WEIGHT	750 LBS.	760 LBS.	875 LBS.	910 LBS.	940 LBS.	940 LBS.	
LENGTH	63 IN.						
WIDTH (W/O CHUTE)	33 IN.	36.5 IN.	50 IN.	55.5 IN.	63 IN.		
WIDTH (W/ CHUTE)	44.5 IN.	49 IN.	62.25 IN.	67.75 IN.	75.75 IN.		
HEIGHT	48 IN.		50.5 IN.				
WARRANTY							
UNIT	5 YEAR COMMERCIAL / 1000 HOUR / NO HOUR LIMIT FIRST 2 YEARS						
DECK SHELL & FRAME	LIMITED LIFETIME						
ATTACHMENTS & ACCESSORIES							
MULCHING KIT, OPERATOR CONTROLLED DISCHARGE BAFFLE, GRASS COLLECTOR SYSTEM, HEADLIGHT KIT, TRIMMER HOLDER, BUCKET HOLDER, BACKPACK BLOWER HOLDER							



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télé. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-WALK®

	32GR	36GR	48GR	36HR	48HE	52HE	60HE
MODEL NUMBER	988150	988151	988152	988184	988185	988186	988187
ENGINE	KAWASAKI® FS481V			KAWASAKI® FS481V	KAWASAKI® FS600V		KAWASAKI® FS691V
HORSEPOWER	14.5 HP			14.5 HP	18.5 HP	18.5 HP	23 HP
DISPLACEMENT	603 CC			603 CC	603 CC	603 CC	726 CC
DRIVE SYSTEM	PEERLESS GEAR DRIVE			HYDRO-GEAR® ZT-2800 TRANSAXLE			
FUEL CAPACITY	5.8 GAL.			5.5 GAL.			
GROUND SPEED (APPROX.Mph)(Forward/Reverse)	5.4 MPH / REVERSE ASSIST			8 MPH / 3 MPH			
STARTER	RECOIL			ELECTRIC			
DECK							
DECK MATERIAL	7 GA.			10 GA.			
DECK CONSTRUCTION	FABRICATED			FABRICATED			
NUMBER OF SPINDLES	2		3	2	3		
BLADE TIP SPEED (FPM)	18,500	18,152	18,500	18,000			
SPINDLE HOUSING MATERIAL	ALUMINUM			FORGED ALUMINUM			
SPINDLE BEARINGS	BALL BEARING			BALL BEARING			
DECK ENGAGEMENT	ELECTRIC CLUTCH			ELECTRIC CLUTCH			
DECK LIFT SYSTEM	MANUAL			MANUAL			
CUTTING WIDTH	32 IN.	36 IN.	48 IN.	36 IN.	48 IN.	52 IN.	60 IN.
CUTTING HEIGHTS	1.5 IN. - 4.5 IN.			1.5 IN. - 4.5 IN.	1.5 IN. - 5.0 IN.		
CUTTING POSITIONS (1/4 IN. Increments)	13			13	15		
WHEELS							
FRONT WHEELS	9 X 3.50-4 SEMI-PNEUMATIC			11 X 4-5 SEMI-PNEUMATIC			
REAR	13 X 5-6	13 X 6.5-6	13 X 6.5-6	21 X 7-10	20 X 8-10		
MACHINE							
WEIGHT	504 LBS.	504 LBS.	572 LBS.	701 LBS.	740 LBS.	770 LBS.	795 LBS.
LENGTH	77 IN.			80.5 IN.	75.5 IN.	77.5 IN.	78.3 IN.
WIDTH	45.7 IN.	48.4 IN.	60.8 IN.	36.8 IN.	50 IN.	55 IN.	63 IN.
HEIGHT	41.9 IN.			45 IN.			
WARRANTY							
UNIT	2 YEAR LIMITED COMMERCIAL			4 YEAR COMMERCIAL / 750 HOUR NO HOUR LIMIT FIRST 2 YEARS			
DECK SHELL & FRAME	N/A						
ATTACHMENTS & ACCESSORIES							
MULCHINGKIT,CLOTHGRASSCOLLECTOR,GRASSCATCHERATTACHMENTBRACKET,OPERATORCONTROLLEDDISCHARGEBAFFLESINGLEWHEELSULKY,TWOWHEELSULKY(SINGLEANDTWOWHEELSULKY'SAVAILABLEONHYDROONLY)							



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

PRO-QXT[®] TRACTOR ATLAS JSV[®]

MODEL NUMBER	985911
ENGINE	KOHLER [®]
HORSEPOWER	14 HP
DISPLACEMENT	429 CC
DRIVE SYSTEM	HYDRO-GEAR [®] ZT - 2800 TRANSAXLES
FUEL CAPACITY	1.8 GAL.
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	5 MPH / 2 MPH
STARTER	ELECTRIC & RECOIL
TIRES	
REAR	TURF 20 X 8 - 10
MACHINE	
WEIGHT (W/O FUEL)	520 LBS.
LENGTH	55.5 IN.
WIDTH	30.5 IN.
HEIGHT	39 IN.
PTO COUPLER	
PTO SPEED	900 RPM
ENGAGEMENT	ELECTRIC
PTO DRIVE	DUAL BELT
FEATURES	
HOURLY METER	STANDARD
POWER STEERING	STANDARD
POWER STEERING LOCK OUT	STANDARD
WARRANTY	
TRACTOR	4 YEAR / 500 HOUR COMMERCIAL NO HOUR LIMIT FIRST 2 YEARS
ENGINE	5 YEAR LIMITED
ACCESSORIES	
WORK LIGHT, TIRE CHAIN, AG TIRES, TWIST GRIP RING	

ATTACHMENTS	MODEL	WIDTH
DOZER BLADE	885910	48 IN.
POWER BRUSH	885911	44 IN.
SNOW BLOWER	885912	32 IN.
BRUSH MOWER	885913	32 IN.
FINISH MOWER	885914	36 IN.
FINISH MOWER	885915	48 IN.
AERATOR	885916	32 IN.
DETHATCHER	885917	27 IN.

	3200	3400	3400SD	6400
MODEL NUMBER	996206	996205	996204	996207
ENGINE	POLARIS [®] 2-CYLINDER, DOHC, GAS			
HORSEPOWER	40 HP			
DISPLACEMENT (CC)	999 CC			
DRIVE SYSTEM	ON-DEMAND TRUE AWD/2WD/VERSATRAC TURF MODE			
FUEL CAPACITY	11.5 GAL.			
GROUND SPEED (APPROX. Mph)	35 MPH			
STARTER	ELECTRIC IGNITION			
TIRES & WHEELS				
FRONT & REAR SUSPENSION	IFS DUAL A-ARM			
FRONT & REAR TIRES	26 X 10 HEAVY DUTY			
FRONT & REAR WHEELS	12 X 6 STEEL			
FEATURES				
STEERING	RACK & PINION		ELECTRIC POWERED STEERING	
BED LIFT	SHOCK ASSIST		STANDARD ELECTRIC	
BED MATERIAL	POLY		STEEL	POLY
FRONT BUMPER	STANDARD, HEAVY DUTY			
HITCH	STANDARD, HEAVY DUTY			
ROPS	ACCORDING TO ANSI/OPEI B71.9, OSHA 1928.53			
VEHICLE DIMENSIONS				
WEIGHT	1,475 LBS.		1,775 LBS.	
LENGTH	122 IN.		155 IN.	
WIDTH			63 IN.	
HEIGHT			73 IN.	
WHEEL BASE	84 IN.	116 IN.	84 IN.	116 IN.
GROUND CLEARANCE	10.5 IN.			
WARRANTY				
UNIT	1 YEAR LIMITED COMMERCIAL			
INSTRUMENTATION				
SPEEDOMETER, TACHOMETER, FUEL GAUGE, HOUR METER, ODOMETER & TRIP METER, GEAR INDICATION, SEATBELT REMINDER LIGHT, BATTERY VOLTAGE CHARGE SYSTEM, ENGINE/COOLANT TEMP, 2 IN-DASH 12V POWER OUTLETS				



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

ZT X

	42	52	52	60
MODEL NUMBER	915255	915256	915257	915274
ENGINE	KOHLER® 7000 PRO TWIN		KAWASAKI® FR691	
HORSEPOWER	22 HP	24 HP	23 HP	
DISPLACEMENT	725 CC		726 CC	
DRIVE SYSTEM	HYDRO-GEAR® EZT TRANSAXLES			
FUEL CAPACITY	2.8 GAL.			
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	7 MPH / 3 MPH			
DECK				
DECK MATERIAL	11 GA.			
DECK CONSTRUCTION	FABRICATED			
NUMBER OF SPINDLES	3			
BLADE TIP SPEED (FPM)	17,000			
SPINDLE HOUSING MATERIAL	STEEL MACHINED			
SPINDLE BEARINGS	SEALED			
DECK ENGAGEMENT	ELECTRIC WARNER®			
DECK LIFT SYSTEM	FOOT OPERATED, DIAL SELECTION			
CUTTING WIDTH	42 IN.	52 IN.	52 IN.	60 IN.
CUTTING HEIGHT	1.5 IN. - 4.5 IN.			
CUTTING POSITIONS	13			
WHEELS				
FRONT	11 X 6-5			
REAR	20 X 8-8	20 X 10-8		
FEATURES				
SEAT	PLUSH HIGH BACK 18 IN. W/ SEAT SPRINGS & ARM REST		PLUSH HIGH BACK 18 IN. W/SEATSPRINGS,LEVERADJUST,ARMRESTS	
HOURLY METER	STANDARD			
MACHINE				
WEIGHT	570 LBS.	615 LBS.	605 LBS.	634 LBS.
LENGTH	77.5 IN.			
WIDTH	54.2 IN.	63.4 IN.		73 IN.
HEIGHT	40.9 IN.			
WARRANTY				
UNIT	3 YEARS OR 300 HOURS			
ATTACHMENTS & ACCESSORIES				
2-BAGPOWEREDBAGGER,MULCHKIT,L.E.D.LIGHTKIT,FLEX-TEND®SHOULDERSSUPPORTSYSTEM,CHROMEREARWHEELCOVERS,48-IN.PLUGAERATOR,36-IN.POLYROLLER,48-IN.DETHATCHER,15-GALLON SPRAYER, TOW-BEHIND SPREADER, TRAILER HITCH KIT				



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

ZT XL

	42	42	48	52	52	60	60
MODEL NUMBER	915259	915262	915261	915258	915263	915260	915264
ENGINE	KOHLER® 7000 PRO TWIN W/ SMART CHOKE™	KAWASAKI® FR651	KAWASAKI® FR691	KOHLER® 7000 PRO TWIN W/ SMART CHOKE™	KAWASAKI® FR691	KOHLER® 7000 PRO TWIN W/ SMART CHOKE™	KAWASAKI® FR730
HORSEPOWER	24 HP	21.5 HP	23 HP	25 HP	23 HP	26 HP	24 HP
DISPLACEMENT	725 CC	726 CC	726 CC	725 CC	726 CC	725 CC	726 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-2800 TRANSAXLES & 7 IN. FANS						
FUEL CAPACITY	2.8 GAL.						
GROUNDSPEED(APPROX.Mph) (Forward/Reverse)	7.5 MPH / 3 MPH						
DECK							
DECK MATERIAL	11 GA.						
DECK CONSTRUCTION	FABRICATED						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	17,000						
SPINDLEHOUSING MATERIAL	STEEL MACHINED						
SPINDLE BEARINGS	SEALED						
DECK ENGAGEMENT	ELECTRIC WARNER®						
DECK LIFT SYSTEM	FOOT OPERATED						
CUTTING WIDTH	42 IN.	42 IN.	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHT	1.5 IN. - 4.5 IN.						
CUTTING POSITIONS	13						
WHEELS							
FRONT	11 X 6-5						
REAR	20 X 8-10			20X10-10		20 X 12-10	
FEATURES							
SEAT	18 IN. PLUSH HIGH BACK W/ PADDED ARM RESTS, SEAT ISOLATION STANDARD						
HOUR METER	STANDARD						
MACHINE							
WEIGHT	615 LBS.		612 LBS.	630 LBS.		645 LBS.	
LENGTH	69 IN.						
WIDTH (W/CHUTE)	58 IN.	58 IN.	64 IN.	68 IN.		75 IN.	
HEIGHT	42 IN.						
WARRANTY							
UNIT	4 YEARS / 400 HOURS						
ATTACHMENTS & ACCESSORIES							
2-BAGPOWEREDBAGGER,BAGGERADAPTER(60"MODELONLY),MULCHKIT,LEDLIGHTKIT,FLEX-TEND*SHOULDERSUPPORTSYSTEM,CHROMEFRONTWHEELCOVERS,CHROMEREARWHEELCOVERS,48-INPLUGAERATOR,36-IN.POLYROLLER, 48-IN. DETHATCHER, 15-GALLONSPRAYER, TOW-BEHIND SPREADER, TRAILER HITCH KIT							



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Télééc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca

SPECIFICATIONS

ZT HD

	44	48	48	52	52	60	60
MODEL NUMBER	991160	991162	991152	991164	991154	991166	991156
ENGINE	KAWASAKI® FR651	KAWASAKI® FRTWIN	KOHLER® 7000 PROTWIN W/ SMART CHOKE™	KAWASAKI® FR TWIN	KOHLER® 7000 PROTWIN W/ SMART CHOKE™	KAWASAKI® FR TWIN	KOHLER® 7000 PROTWIN W/ SMART CHOKE™
HORSEPOWER	21.5 HP	23 HP	25 HP	23 HP	25 HP	24 HP	26 HP
DISPLACEMENT	726 CC	726 CC	725 CC	726 CC	725 CC	726 CC	725 CC
DRIVE SYSTEM	HYDRO-GEAR® ZT-3100 TRANSAXLES						
FUEL CAPACITY	5.0 GAL.						
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	8 MPH / 4 MPH						
DECK							
DECK MATERIAL	10 GA.						
DECK CONSTRUCTION	WELDED						
NUMBER OF SPINDLES	3						
BLADE TIP SPEED (FPM)	18,000						
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM						
SPINDLE BEARINGS	BALL BEARING						
DECK ENGAGEMENT	ELECTRIC OGURA®						
DECK LIFT SYSTEM	FOOT OPERATED						
CUTTING WIDTH	44 IN.	48 IN.	48 IN.	52 IN.	52 IN.	60 IN.	60 IN.
CUTTING HEIGHT	1.5 IN. - 5.0 IN.						
CUTTING POSITIONS	15						
WHEELS							
FRONT	13 X 6.5-6	13 X 5-6	13 X 6.5-6				
REAR	22 X 10-12			22 X 10.5-12		22 X 12-12	
FEATURES							
SEAT	20 IN. PLUSH HIGH BACK COMFORT , LEVER ADJUST, PADDED ARM RESTS						
HOURLY METER	STANDARD						
MACHINE							
WEIGHT	805 LBS.	825 LBS.		850 LBS.		870 LBS.	
LENGTH	79 IN.						83 IN.
WIDTH (W/CHUTE)	56 IN.	63 IN.		67 IN.		75 IN.	
HEIGHT	47 IN.						
WARRANTY							
UNIT	4 YEARS / 500 HOURS						
ATTACHMENTS & ACCESSORIES							
2-BAG POWERED BAGGER, BAGGER MOUNT KIT, MULCH KIT, OPERATOR-CONTROLLED CHUTE BAFFLE, DISCHARGE COVER KIT, VACUUM BAFFLE KIT, LAWN STRIPING KIT, LIGHT KIT, FLEX-TEND® SHOULDERSUPPORTS SYSTEM, SEAT ISOLATOR KIT, SEAT SPRING KIT, FOLDING PROPS KIT, SUNSHADE, CHROME FRONT WHEEL COVERS, CHROME REAR WHEEL COVERS, TRAILER HITCH KIT, 48-IN. PLUG AERATOR, 36-IN. POLY ROLLER, 48-IN. DETHATCHER, 15-GALLON SPRAYER, TOW-BEHIND SPREADER							



Distribué par / Distributed by :



MTI Canada

Tél. / tel.: 418 839-4127

Français: 1 800 463-4398

English: 1 800 463-7205

Téléc. / Fax: 1 800 363-7157

www.mticanada.ca • info@mticanada.ca