



# 2020-2021 SPECIFICATIONS

## **PRODUCT SPECIFICATIONS**

			RAPIDTRAK		RAPIDTRAK	
DESIGNATION	PROFESSIONAL 28	PROFESSIONAL 28 HYDRO EFI	PROFESSIONAL 28 HYDRO RAPIDTRAK <sup>®</sup>	PROFESSIONAL 32	PROFESSIONAL 32 HYDRO RAPIDTRAK®	PLATINUM 24 SHO
MODEL #	926077	926068	926078	926076	926079	921050
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE
ENGINE POWER	420CC (21 FT/LBS)	420CC (21 FT/LBS)	420CC (21 FT/LBS)	420CC (21 FT/LBS)	420CC (21 FT/LBS)	369CC GEN 3 (17 FT/LBS)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX
STARTING SYSTEM	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL
CLEARING WIDTH	28 IN (71.2 CM)	28 IN (71.2 CM)	28 IN (71.2 CM)	32 IN (81.3 CM)	32 IN (81.3 CM)	24 IN (61 CM)
HOUSING HEIGHT	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)	21 IN (53.3 CM)
THROWING DISTANCE	3 - 60 FT (.9-18.2 M)	3 - 60FT (.9 - 18.2M)	3 - 60 FT (.9-18.2 M)	3 - 60 FT (.9-18.2 M)	3 - 60 FT (.9-18.2 M)	3 - 55 FT (.9 - 16.7 M)
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°	200°
CHUTE ROTATION	QUICK TURN™	QUICK TURN	QUICK TURN	QUICK TURN	QUICK TURN	QUICK TURN™
DEFLECTOR CONTROL	REMOTE	REMOTE	REMOTE	REMOTE	REMOTE	REMOTE
TIRE SIZE	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	5.5 IN WIDE TRACK (14 CM)	16 X 6.5 IN (41 X 17 CM)	5.5 IN WIDE TRACK (14 CM)	16 X 4.8 IN (41 X 12 CM)
TIRE TYPE	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TREAD
STEERING	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN
DRIVE TYPE	DISC-O-MATIC	HYDROSTATIC	HYDROSTATIC	DISC-O-MATIC	HYDROSTATIC	DISC-O-MATIC
SPEEDS	6 FORWARD / 2 REVERSE	VARIABLE	VARIABLE	6 FORWARD / 2 REVERSE	VARIABLE	6 FORWARD / 2 REVERSE
GEAR CASE	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON
GEAR CASE WARRANTY	5YR RES, 5YR COMM	5 YR RES, 5YR COMM	5YR RES, 5YR COMM	5YR RES, 5YR COMM	5YR RES, 5YR COMM	5YR RES, 1YR COMM
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER DIAMETER	16 IN (40.6 CM)	16 IN (40.6 CM)	16 IN (40.6 CM)	16 IN (40.6 CM)	16 IN (40.6 CM)	14 IN (35.6 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED
SKID SHOES	COMM SKIDS	COMM SKIDS	COMM SKIDS	COMM SKIDS	COMM SKIDS	STEEL REVERSIBLE
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 1YR COMM	3YR RES, 1YR COMM	3YR RES, 1YR COMM	3YR RES, 1YR COMM	3YR RES, 1YR COMM	3YR RES, 90DAY COMM
LENGTH	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)	58.3 IN (148.1 CM)
WIDTH	30.2 IN (76.7 CM)	30.2 IN (76.7 CM)	30.2 IN (76.7 CM)	34.2 IN (86.9 CM)	34.2 IN (76.7 CM)	26.4 IN (67.1 CM)
HEIGHT	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)	45.9 IN (116.6 CM)
WEIGHT	307 LBS (139.3 KG)	352 LBS (159.7 KG)	331 LBS (150.1 KG)	314 LBS (142.4 KG)	338 LBS (153.3 KG)	286 LBS (129.7 KG)
OPTIONS OR ACCESSORIES AT A GLANCE	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO- THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO- THRO COVER	FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO- THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO- THRO COVER	FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO- THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER

Distribué par / Distributed by : MTI Canada Tél. / tel: 418 839-4127 Français: 1 800 463-4398 English: 1 800 463-4398 English: 1 800 463-7205 Téléc. / Fax: 1 800 363-7157 www.mticanada.ca • info@mticanada.ca

#### RAPIDTRAK

DESIGNATION	PLATINUM 24 SHO EFI	PLATINUM 30 SHO	PLATINUM 28 SHO RAPIDTRAK®	DELUXE 24	DELUXE 28	DELUXE 28 SHO	DELUXE 30
MODEL #	921053	921051	921057	921045	921046	921048	921047
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE
ENGINE POWER	369CC EZ-LAUNCH EFI (17 FT/LBS)	414CC GEN 3 (20 FT/LBS)	369CC (17 FT/LBS)	254CC (12.5 FT/LBS)	254CC (12.5 FT/LBS)	306CC (15 FT/LBS)	306CC (15 FT/LBS)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX
STARTING SYSTEM	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL
CLEARING WIDTH	24 IN (61 CM)	30 IN (76.2 CM)	28 IN (71.2 CM)	24 IN (61 CM)	28 IN (71.2 CM)	28 IN (71.2 CM)	30 IN (76.2 CM)
HOUSING HEIGHT	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)
THROWING DISTANCE	3 - 55 FT (.9 - 16.7 M)	3 - 55 FT (.9 - 16.7 M)	3 - 55 FT (.9 - 16.7 M)	3 - 50 FT (.9 - 15.2 M)	3 - 50 FT (.9 - 15.2 M)	3 - 55 FT (.9 - 16.7 M)	3 - 50 FT (.9 - 15.2 M)
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°	200°	200°
CHUTE ROTATION	QUICK TURN™	QUICK TURN	QUICK TURN	2.5X ICE DRILL	2.5X ICE DRILL	2.5X ICE DRILL	2.5X ICE DRILL
DEFLECTOR CONTROL	REMOTE	REMOTE	REMOTE	REMOTE	REMOTE	REMOTE	REMOTE
TIRE SIZE	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	5.5 IN WIDE TRACK (14 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 4.8 IN (41 X 12 CM)
TIRE TYPE	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD
STEERING	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN
DRIVE TYPE	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC
SPEEDS	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE
GEAR CASE	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON
GEAR CASE WARRANTY	5 YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED
SKID SHOES	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM
LENGTH	58.3 IN (148.1 CM)	58.3 IN (148.1 CM)	60.3 IN (153.2 CM)	58.6 IN (148.8 CM)	58.6 IN (148.8 CM)	58.6 IN (148.8 CM)	58.3 IN (148.1 CM)
WIDTH	26.4 IN (67.1 CM)	32.4 IN (82.3 CM)	30.2 IN (76.7 CM)	26.4 IN (67.1 CM)	29.9 IN (75.9 CM)	29.9 IN (75.9 CM)	32.4 IN (82.3 CM)
HEIGHT	45.9 IN (116.6 CM)	45.9 IN (116.6 CM)	46.6 IN (118.4 CM)	45.3 IN (115.1 CM)	45.3 IN (115.1 CM)	45.3 IN (115.1 CM)	45.5 IN (115.6 CM)
WEIGHT	286 LBS (129.7 KG)	294 LBS (133.3 KG)	331 LBS (150.1 KG)	245.5 LBS (111.4 KG)	249.8 LBS (113.3 KG)	267.5 LBS (121.3 KG)	275.6 LBS (125 KG)
OPTIONS OR ACCESSORIES AT A GLANCE	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, TIRE CHAINS, TRACK, DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	HANDWARMER KIT, TIRE CHAINS, TRACK, DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACH DRIVE CONVERSION KIT, FRONT WEIGHT KIT, DRIFT CUTTER KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER

Distribué par / Distributed by :

Mail
<th

## **PRODUCT SPECIFICATIONS**

			RAPIDTRAK.				
DESIGNATION	DELUXE 30 EFI	COMPACT 24	COMPACT 24 RAPIDTRAK®	CLASSIC 24	CLASSIC 24+	CROSSOVER 20	PROFESSIONAL 21 SSR
MODEL #	921049	920029	920028	920025	920030	932050	938024
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	SINGLE STAGE
ENGINE POWER	306 CC EZ-LAUNCH EFI (15 FT/LBS)	223CC (10 FT/LBS)	223CC (10 FT/LBS)	208CC (9.5 FT/LBS)	223CC (10 FT/LBS)	179CC (8.25 FT/LBS)	208CC (9.5 FT/LBS)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX
STARTING SYSTEM	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	RECOIL
CLEARING WIDTH	30 IN (76.2 CM)	24 IN (61 CM)	24 IN (61 CM)	24 IN (61 CM)	24 IN (61 CM)	20 IN (50.8 CM)	21 IN (53.3 CM)
HOUSING HEIGHT	21 IN (53.3 CM)	20 IN (50.8 CM)	20 IN (50.8 CM)	20 IN (50.8 CM)	20 IN (50.8 CM)	19 IN (48.3 CM)	12.1 IN (30.7 CM)
THROWING DISTANCE	3 - 50 FT (.9-15.2 M)	3 - 40 FT (.9 - 12.2 M)	3 - 40 FT (.9 - 12.2 M)	3 - 40 FT (.9 - 12.2 M)	3 - 40 FT (.9 - 12.2 M)	3 - 35 FT (.9 - 10.7 M)	3 - 35 FT (.9 - 10.7 M)
CHUTE TURNING RADIUS	200°	205°	205°	205°	205°	205°	210°
CHUTE ROTATION	2.5X ICE DRILL	2.5X QUICK TURN	2.5X QUICK TURN	2.5X QUICK TURN	2.5X QUICK TURN	MANUAL	MANUAL
DEFLECTOR CONTROL	REMOTE	REMOTE	REMOTE	REMOTE	REMOTE	MANUAL	MANUAL
TIRE SIZE	16 X 4.8 IN (41 X 12 CM)	15 X 5 IN (38 X 13 CM)	5.5 IN WIDE TRACK (14 CM)	13 X 4 IN (33 X 10 CM)	15 X 5 IN (38.1 X 12.7 CM)	14 X 1.75 IN (35.6 X 4.5 CM)	7.5 X 2 IN (19.1 X 5.1 CM)
TIRE TYPE	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK	POLAR TRAC	POLAR TRAC	DIAMOND	N/A
STEERING	AUTO-TURN	AUTO-TURN	SOLID LOCKED	PIN LOCK	PIN LOCK	SOLID UNLOCKED	SOLID UNLOCKED
DRIVE TYPE	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	DISC-O-MATIC	AUGER PROPELLED	AUGER PROPELLED
SPEEDS	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	1 FORWARD	1 FORWARD
GEAR CASE	CAST IRON	CAST IRON	CAST IRON	ALUMINUM	CAST IRON	ALUMINUM	N/A
GEAR CASE WARRANTY	5YR RES, 1YR COMM	5YR RES, 1YR COMM	5YR RES, 1YR COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	N/A
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	14 IN (35.6 CM)	12 IN (30.5 CM)	12 IN (30.5 CM)	12 IN (30.5 CM)	12 IN (30.5 CM)	10 IN (25.4 CM)	N/A
AUGER DIAMETER	14 IN (35.6 CM)	11 IN (27.9 CM)	11 IN (27.9 CM)	11 IN (27.9 CM)	11 IN (27.9 CM)	11 IN (27.9 CM)	8.375 IN (21.3 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL WITH RUBBER LINING	REINFORCED RUBBER
SKID SHOES	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	STEEL REVERSIBLE	N/A	N/A
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	POLYMER ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 1YR COMM
LENGTH	58.3 IN (153.2 CM)	53.8 IN (136.6 CM)	53.3 IN (135.4 CM)	54.4 IN (138.2 CM)	54.4 IN (138.2 CM)	48 IN (121.9 CM)	50.8 IN (128.9 CM)
WIDTH	32.4 IN (76.7 CM)	26.4 IN (67.1 CM)	26.4 IN (67.1 CM)	26.4 IN (67.1 CM)	26.4 IN (67.1 CM)	21 IN (53.3 CM)	21.2 IN (53.8 CM)
HEIGHT	45.5 IN (118.4 CM)	44 IN (111.8 CM)	43.4 IN (110.2 CM)	42.9 IN (109 CM)	42.9 IN (109 CM)	42 IN (106.7 CM)	41.7 IN (105.9 CM)
WEIGHT	275.6 LBS (125 KG)	187 LBS (84.8 KG)	220 LBS (99.8 KG)	180 LBS (81.6 KG)	180 LBS (81.6 KG)	129 LBS (58.5 KG)	87 LBS (39.46 KG)
OPTIONS OR ACCESSORIES AT A GLANCE		HANDWARMER KIT, TIRE CHAINS, FRONT WEIGHT KIT, SNO-THRO CAB, SNO-THRO COVER, COMPOSITE SKID SHOES, DRIFT CUTTER KIT	HANDWARMER KIT, DRIFT CUTTER KIT, FRONT WEIGHT KIT, COMPOSITE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER			SNO-THRO COVER, DRIFT CUTTER KIT	

Distribué par / Distributed by : MTI Canada Tél. /tel.: 418 839-4127 Français: 1 800 463-4398 English: 1 800 463-7205 Téléc. / Fax: 1 800 363-7157 www.mticanada.ca • info@mticanada.ca

DESIGNATION	PROFESSIONAL 21 SSRC	S18	PATH-PRO <sup>®</sup> 208E	PATH-PRO <sup>®</sup> 208EC	POWER BRUSH 28	POWER BRUSH 36	POWER BRUSH 36 HYDRO
MODEL #	938025	938026	938032	938033	921056	926074	926075
STAGE TYPE	SINGLE STAGE	SINGLE STAGE	SINGLE STAGE	SINGLE STAGE	N/A	N/A	N/A
ENGINE POWER	208CC (9.5 FT/LBS)	99CC (4.1 FT/LBS)	208CC (9.5 FT/LBS)	208CC (9.5 FT/LBS)	177CC	277CC	277CC
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	KOHLER CH255	KOHLER CH395	KOHLER CH395
STARTING SYSTEM	RECOIL	RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	120V/RECOIL	12V KEY START & RECOIL
CLEARING WIDTH	21 IN (53.3 CM)	18 IN (45.7 CM)	21 IN (53.3 CM)	21 IN (53.3 CM)	28 IN (71.2 CM)	36 IN (91.4 CM)	36 IN (91.4 CM)
HOUSING HEIGHT	12.1 IN (30.7 CM)	12 IN (30.5 CM)	12.2 IN (31 CM)	12.2 IN (31 CM)	N/A	N/A	N/A
THROWING DISTANCE	3 - 35 FT (.9 - 10.7 M)	3 - 25 FT (.9 - 7.6 M)	3 - 35 FT (.9 - 10.7 M)	3 - 35 FT (.9 - 10.7 M)	N/A	N/A	N/A
CHUTE TURNING RADIUS	210°	210°	210°	210°	N/A	N/A	N/A
CHUTE ROTATION	REMOTE	MANUAL	MANUAL	REMOTE	N/A	N/A	N/A
DEFLECTOR CONTROL	MANUAL	MANUAL	MANUAL	MANUAL	N/A	N/A	N/A
TIRE SIZE	7.5 X 2 IN (19.1 X 5.1 CM)	6 X 1.5 IN (15.2 X 3.8 CM)	7.5 X 1.75 IN (19.1 X 4.4 CM)	7.5 X 1.75 IN (19.1 X 4.4 CM)	16 X 4.8 IN (41 X 12 CM)	16 X 6.5 IN (41 X 17 CM)	16 X 6.5 IN (41 X 17 CM)
TIRE TYPE	N/A	N/A	N/A	N/A	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TREAD
STEERING	SOLID UNLOCKED	SOLID UNLOCKED	SOLID UNLOCKED	SOLID UNLOCKED	AUTO-TURN	AUTO-TURN	AUTO-TURN
DRIVE TYPE	AUGER PROPELLED	AUGER PROPELLED	AUGER PROPELLED	AUGER PROPELLED	DISC-O-MATIC	DISC-O-MATIC	HYDROSTATIC
SPEEDS	1 FORWARD	1 FORWARD	1 FORWARD	1 FORWARD	6 FORWARD / 2 REVERSE	6 FORWARD / 2 REVERSE	VARIABLE
GEAR CASE	N/A	N/A	N/A	N/A	N/A	CAST ALUMINUM	CAST ALUMINUM
GEAR CASE WARRANTY	N/A	N/A	N/A	N/A	N/A	N/A	N/A
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	N/A	N/A	N/A
IMPELLER DIAMETER	N/A	N/A	N/A	N/A	N/A	N/A	N/A
AUGER DIAMETER	8.375 IN (21.3 CM)	7.0 IN (17.8 CM)	8.375 IN (21.3 CM)	8.375 IN (21.3 CM)	18 IN (45.7 CM)	25 IN (63.5 CM)	25 IN (63.5 CM)
AUGER TYPE	REINFORCED RUBBER	REINFORCED RUBBER	REINFORCED RUBBER	REINFORCED RUBBER	BRUSH	BRUSH	BRUSH
SKID SHOES	N/A	N/A	N/A	N/A	N/A	N/A	N/A
SCRAPER BAR	POLYMER ADJUSTABLE	POLYMER FIXED	POLYMER ADJUSTABLE	POLYMER ADJUSTABLE	N/A	N/A	N/A
PRODUCT WARRANTY	3YR RES, 1YR COMM	2YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 90DAY COMM	3YR RES, 1YR COMM	3YR RES, 1YR COMM
LENGTH	50.8 IN (128.9 CM)	44 IN (118.8 CM)	54.3 IN (137.9 CM)	54.3 IN (137.9 CM)	65 IN (165.1 CM)	72 IN (183 CM)	72 IN (183 CM)
WIDTH	21.2 IN (53.8 CM)	20 IN (50.8 CM)	21.6 IN (54.9 CM)	21.6 IN (54.9 CM)	33 IN (83.8 CM)	44 IN (111.8 CM)	44 IN (111.8 CM)
HEIGHT	41.7 IN (105.9 CM)	37 IN (94 CM)	40.9 IN (103.9 CM)	40.9 IN (103.9 CM)	44 IN (111.8 CM)	43 IN (109.2 CM)	43 IN (109.2 CM)
WEIGHT	89 LBS (39.46 KG)	59 LBS (26.76 KG)	95 LBS (43.1 KG)	97 LBS (43.9 KG)	238 LBS (107.9 KG)	373 LBS (169.19 KG)	403 LBS (182.8KG

FLOOR MAT, REMOTE CHUTE ROTATION KIT, SNO-THRO COVER, HIGH WEAR PADDLES

FLOOR MAT,

SNO-THRO COVER

OPTIONS OR ACCESSORIES AT A GLANCE

Distributé par / Distributed by : MTI Canada TÉL / tel: 418 839-4127 Fançais: 1 800 463-4398 English: 1 800 463-7205 Téléc. / Fax: 1 800 363-7157 www.mticanada.ca • info@mticanada.ca